

Bush Hog® TOUGH

3226QT Quick Attach Front-Push Loaders

Bush Hog Quick Attach System

BUSH HOG® TOUGH FEATURES

TOUGH Boxed Boom Design

TOUGH Large Diameter Cross Tubes

TOUGH Robotic Welds

TOUGH High Strength Chrome Plated Cylinder Rods

TOUGH Bush Hog Made Buckets

TOUGH Powder Coat Paint



| MODEL | Specifications Based on 1997 ASAE STANDARDS | 3226QT |
|---|--|------------|
| Tractor PTO HP Range | | 70 - 120 |
| 2WD/FWA | | 2WD only |
| Maximum Lift Height - Measured at Pivot Pin | | 143 inches |
| Maximum Lift Height - Under Level Bucket | | 134 inches |
| Maximum Dump Angle | | 50° |
| Digging Depth | | 4.5 inches |
| Lift Capacity to Maximum Height - At Pivot Pin | | 4110 lbs |
| Lift Capacity to Maximum Height - 31.5 inches Forward of Pivot Pin | | 2800 lbs |
| Lift Capacity to 59 inch Height - At Pivot Pin | | 4410 lbs |
| Lift Capacity to 59 inch Height - 31.5 inches Forward of Pivot Pin | | 3360 lbs |
| Breakout Force - At Pivot Pin | | 5160 lbs |
| Breakout Force - 31.5 inches - Forward of Pivot Pin | | 3730 lbs |
| Rollback Force at Maximum Height - 31.5 inches Forward of Pivot Pin | | 4940 lbs |
| Rollback Force at 59 inch Height - 31.5 inches Forward of Pivot Pin | | 6865 lbs |
| Rollback Force at Ground Level - 31.5 inches Forward of Pivot Pin | | 5305 lbs |
| Raising Time (Ground Level to Full Height) | | 5 seconds |
| Lowering Time (Full Height to Ground Level) | | 3 seconds |
| Bucket Dumping Time (Full Rollback to Full Dump) | | 5 seconds |
| Bucket Rollback Time (Full Dump to Full Rollback) | | 3 seconds |
| Hydraulics | Two 2.5 inch Bore, 28.75 inch Stroke Double Acting Bucket Cylinders and Two 2.5 inch Bore, 31.5 inch Stroke Double Acting Lift Cylinders | |
| Specifications Based on Tractor System of | 2450 PSI hyd. pressure & 16 GPM pump capacity | |
| Bush Hog Quick Attach Buckets | Available in 60, 72 and 84 inch widths | |
| Bush Hog Quick Attach Heavy Duty Bucket | Available in 84 inch widths | |
| Options | Forklift (48 inch tines) Attachment, Round Bale Spear, Grapple Fork, Bucket Tine Teeth, Bolt-On Digging Teeth, Side Cutting Edges, Spill Guard Attachment, Hydraulic Self-Leveling, and Grill Guards | |
| Warranty | 1 year limited warranty | |
| FEATURES | Available in major tractor colors | |

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE